#### **Internal Hard Drives**

# S300 Surveillance Hard Drive

### Capture every detail



10 8 6 5 4 TB TB TB TB TB

Color



Toshiba's 3.5-inch S300 Surveillance Hard Drive is designed and tested for 24/7 reliable surveillance, built for speed, capacity, and longer content retention. Capture and analyse every frame from up to 64 video cameras in high resolution with the S300. Space is important to continually capture a history of video evidence over a period of time. With up to 10 TB you get the capacity to record and play back the events in real-time in high resolution and with object identification and face recognition.

#### Use for

- Surveillance Digital Video Recorders (sDVR)
- Surveillance Network Video Recorders (sNVR)
- Hybrid sDVR (analog and IP)
- RAID Storage Arrays for Surveillance



TA 3.5" SATA Hard Drive

**RPM** 7200 / 5400 rpm

256 / 128 MB buffer

24/7 operation

Supports up to 64 video cameras

High reliability and enhanced real-time performance

Toshiba Dynamic Cache Technology
Toshiba Stable Platter Technology

High-endurance design

3-year warranty

### Manual

Toshiba Installation and Safety.pdf 🕹

### Tools

TOSHIBA Storage Diagnostic Tool.zip 🕹





# **Product Specifications**



Basic	Spe	cifica	ations

Reliability

Workloads

MTTF

Form factor	3.5-inch		
Interface	6.0 Gbit/s		
Number of cameras supported	64 (6 TB -10 TB), 32 (4 TB, 5 TB)		
Max. transfer rate	248 MB/s Typ. (10 TB), 241 MB/s Typ. (6 TB, 8 TB) 157 MB/s Typ. (4 TB, 5 TB)		
Drive bays supported	8+ (6 TB -10 TB), 1-8 (4 TB, 5 TB)		
Rotational Vibration (RV) Sensors	Yes		
Advanced Format (AF)	Yes		
RoHS compatible	Yes		
Halogen Free	Yes		
Shock Sensor	Yes		
Performance			
Rotational speed	7200 rpm (6 TB - 10 TB), 5400 rpm (4 TB, 5TB)		
Buffer size	256 MB (6 TB - 10 TB), 128 MB (4 TB, 5 TB)		
Average latency	4,17 ms (6 TB - 10 TB), 5,56 ms (4 TB, 5 TB)		
Native Command Queing (NCQ)	Supported		

180 TB/year (6 TB - 10 TB),

110 TB/year (4 TB, 5 TB) 1.000.000 hours

Unrecoverable error rate	1 per 10E14 bits read Yes		
24/7 operation			
Load / Unload Cycle	600.000		
Limited warranty	3 years		
Power Management			
Supply voltage	5V DC +6/-5%; 12V DC ±10% (6TB - 10TB); 5V DC ±5%; 12V DC ±10% (4TB, 5TB)		
Consumption - Read/Write	9.48 W typ. (10 TB), 8.61 W typ. (8 TB), 7.88 W typ. (6 TB), 7.5 W typ. (4 TB, 5 TB)		
Consumption - Low Power Idle	7.15 W typ. (10 TB), 6.33 W typ. (8 TB), 5,59 W typ. (6 TB), 4.00 W typ. (4 TB, 5 TB)		
Environmental			
Temperature (operating / non-operating)	0 - 70° C / -40 - 70° C		
Vibration (operating)	0.75 G (5 to 300 Hz) 0.25 G (300 to 500 Hz)		
Vibration (non-operating)	3.0 G (5 to 500Hz) (6 TB - 10 TB); 5 G (5 to 500Hz) or less (4 TB, 5 TB)		
Shock (operating)	70 G / 2 ms duration		
Shock (non-operating)	250 G / 2 ms duration (6 TB - 10 TB), 300 G / 2 ms duration (4 TB, 5 TB)		
Acoustics (idle mode)	34 dB typ. (6 TB - 10 TB), 26 dB typ. (4 TB, 5 TB)		
Physical			
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm		
Weight (approx.)	770 g max. (6 TB - 10 TB), 720 g max. (4 TB, 5 TB)		

Box Content	3.5-inch internal HDD - S300	
	Surveillance Hard Drive	

### **Product Range**

Part num	ber	Capacity	Color
HDWT31A	UZSVA (Bulk)	10 TB	-
HDWT380	UZSVA (Bulk)	8 TB	-
HDWT360	UZSVA (Bulk)	6 TB	-
HDWT150	UZSVA (Bulk)	5 TB	-
HDWT140	UZSVA (Bulk)	4 TB	-

### Logistical Information:

Box dimensions Box weight (gross)

321 x 406 x 213 mm

Master carton dimensions Master carton weight (gross) 16 kg (typ.), 11 kg (typ.) (1TB, 500GB)

Boxes per master carton 20 Pallet dimensions n/A Pallet weight (net) n/A Units per pallet 180

### Contact

Toshiba Electronics Europe GmbH

Hansaallee 181 40549 Düsseldorf Germany