

DATASHEET

H2S IP Phone

The Fanvil H2S IP Phone is a Hotel phone with succinct design and high cost performance greatly improve work efficiency.

Highlights

- ✓ Concise and fashionable product appearance
- ✓ Economical and Environmental friendly product concepts
- ✓ Easy installation and configuration
- ✓ Support for fast ethernet adaptive 10/100mbps network port, support POE power supply.
- ✓ High Interoperability Compatible with major platforms: 3CX, Broadsoft, Elastix, Asterisk, Xorcom, etc.

Model	Screen	Network	POE	Supply Power
H2S	N/A	10/100Mbps	٧	×



IP Configuration: Static / DHCP / PPPoE

Network Access Control: 802.1x

VPN: L2TP / OpenVPN

SIP2.0 over UDP/TCP/TLS

RTP/RTCP/SRTP

VLAN

QoS

STUN

DHCP PPPoE

802.1x

L2TP OpenVPN

SNTP FTP/TFTP

HTTP/HTTPS

Protocols



Generic

- 1 SIP Line
- POE Enable
- Handset mode
- Wall installation
- Optional External Power Supply

Call Features

- Call out / Answer
- Call Hold / Resume
- Call Transfer(Attended/Unattended)
- Redial
- Hot Line
- Hot desking

Phone Features

- Call logs with missed calls/ incoming calls/ outgoing calls. Max support 600 records(web)
- Dial without registration
- Action URL / Active URI
- Web dial

Audio

- Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB
- Acoustic echo cancellation (AEC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band DTMF (RFC2833) / SIP INFO

Deployment & Maintenance

TR-069

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
- Web Management Portal
- Web-based Packet-dump
- Configuration Export / Import
- Firmware Upgrade
- Syslog

Networking

10/100Mbps Ethernet

Fanvil Technology Co., Ltd

Address: 4F, Block A, Building 1#, GaoXinQi Hi-Tech Park (Phase-II), 67th District, Bao'An, Shenzhen, 518100, China

Tel: 0755-2640-2199 Fax: 0755-2640-2618

Sales Email: sales@fanvil.com Support@fanvil.com Web: www.fanvil.com





DATASHEET

Physical Specifications

Keypad: 17 keys, including

> 12 Standard Phone Digits keys

5 Function keys

Handset (RJ11) x1

Standard RJ11 Handset Wire x1

RJ11 Port x1: Handset x1
RJ45 Port x1: Network x1
DC Power Input:: 12V / 0.5A

● Working Temperature: 0~40°C

Working Humidity: 10~95%
Installation: Wall installation

Color: Black

Device Dimensions: 96x222x59mmGift Box Dimensions: 302x105x67mm

• Outer CTN Dimensions: 445x355x325mm (20 PCS)

Power Consumption: Idle 1.6~2.3W, Peak 2.6~3.3W

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products. Customers should consult Fanvil's retailers, distributors, or Fanvil directly, if customers have concerns on any feature. For more information, please visit: www.fanvil.com

Compatibility List:































Fanvil Technology Co., Ltd

Address: 4F, Block A, Building 1#, GaoXinQi Hi-Tech Park (Phase-II), 67th District, Bao'An, Shenzhen, 518100, China

Tel: 0755-2640-2199 Fax: 0755-2640-2618

Sales Email: support@fanvil.com Web: www.fanvil.com

