



## FACT SHEET

# GSX 1200 PRO Audio Amplifier

Designed for the competitive eSports arena, the GSX 1200 PRO audio amplifier features a groundbreaking 7.1. Virtual Surround Algorithm. Experience surround sound on a new level. Precise control of both game and communication sound, allowing separate adjustments and switch between headphones and speakers without unplugging cables. Get ready for the tournament and connect up to 8 GSX 1200 PROs together for hard-wired lag-free communication and control of inbound and outbound chat. It works with PC and Mac.



## FEATURES & BENEFITS

- 7.1 Sennheiser Binaural Rendering Engine – the ultimate positional gaming audio
- Chat Link – connect up to 8 GSX 1200 PROs together for hard-wired lag-free communication
- Aluminium volume wheel and high-quality materials for superior performance
- Switch between your headset and speakers with the touch of a button
- Adjust game and communication audio separately
- Peace of mind – 2-year international warranty

## CONTENT OF DELIVERY

- GSX 1200 PRO audio amplifier
- USB cable
- Chat cable
- Quick Start Guide
- Safety Guide





# GSX 1200 PRO

## Audio Amplifier

### Technical Data

#### GSX 1200 PRO

Art. No.	507080
EAN No.	40 44155 21192 4
UPC No.	6 15104 27672 7
Product description	USB audio amplifier for gaming

#### General Data

USB standard	USB 2.0 full speed & USB audio 1.0
Total harmonic distortion	0.005 % THD @ -3dBFS
Cable length	USB cable: 1.2 m Chat cable: 2.0 m
Connector plugs	mini-USB socket 3.5 mm headset socket 3.5 mm microphone socket 3.5 mm loudspeaker socket 2.5 mm chat interface socket A 2.5 mm chat interface socket B
Compatibility	PC & Mac
Warranty	2 years

#### Supported sample rates

Main Audio	7.1: 44.1 kHz @ 16 bit 7.1: 48.0 kHz @ 16 bit 2.0: 44.1 kHz @ 16 bit 2.0: 48.0 kHz @ 16 bit
Main Audio HD	2.0: 96.0 kHz @ 24 bit
Communication Audio	1.0: 16.0 kHz @ 16 bit

### Spare parts

#### Chat Link Cable

Art. No.	507231
EAN No.	40 44155 22267 8
UPC No.	6 15104 29971 9
Product description	Cable for connecting Chat Link

#### Audio outputs

<b>Headphones</b>	DC coupled & dual rail power supply
- Frequency response	0 – 48.0 kHz
- Recommended headphone impedance	16 – 150 $\Omega$
- Max. output voltage	1 V RMS @ 32 $\Omega$

#### Line out (AUX)

- Frequency response	1.5 Hz – 48.0 kHz
- Max. output voltage	1 V RMS @ 10 $\Omega$

#### Packaging

Dimension of product packaging (L x W x H)	143 x 70 x 139 mm
Package weight (incl. complete product and packaging)	413 g
Dimension of master carton (L x W x H)	378 x 284 x 156 mm
Units in distributor master carton	10
Languages	English, German, French, Spanish, Italian, Dutch and Portuguese