



Overview

Model Name	APC Smart-UPS C 2000VA LCD RM 2U 230V
Includes	CD with software , Documentation CD , Installation guide , Rack Mounting brackets , USB cable
Standard Lead Time	Usually Ships within 2 Weeks
Product Distribution	Afghanistan , Algeria , Angola , Argentina , Armenia , Australia , Azerbaijan , Bahrain , Bangladesh , Belarus , Benin , Bolivia , Botswana , Brazil , Brunei Darussalam , Burkina Faso , Burundi , Cambodia , Cameroon , Central African Republic , Chad , Chile , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cook Islands , Cote D'Ivoire , Djibouti , East Timor , Egypt , Equatorial Guinea , Eritrea , Ethiopia , Falkland Islands (Malvinas) , Gabon , Gambia , Georgia , Ghana , Guadeloupe , Guinea , French Guiana , Hong Kong , Indonesia , Iran (Islamic Republic Of) , Iraq , Israel , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Lebanon , Lesotho , Liberia , Madagascar , Malawi , Malaysia , Mali , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Myanmar , Namibia , Nepal , New Zealand , Niger , Nigeria , Oman , Pakistan , Papua New Guinea , Paraguay , Peru , Philippines , Qatar , Reunion , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Somalia , South Africa , Sri Lanka , Sudan , Suriname , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uruguay , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity	1300 Watts / 2000 VA
Max Configurable Power (Watts)	1300 Watts / 2000 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Sine wave
Output Connections	(2) IEC Jumpers (Battery Backup) , (6) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C20
Input voltage range for main operations	180 - 287 V
Maximum Input Current	0 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Input Breaker Capacity	0 A
------------------------	-----

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 hour(s)
Replacement Battery	APCRBC133
RBC Quantity	1

Communications & Management

Interface Port(s)	USB
Available SmartSlot™ Interface Quantity	0
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	--

Surge Protection and Filtering

Surge energy rating	300 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	89.0 mm
Maximum Width	480.0 mm
Maximum Depth	470.0 mm
Rack Height	2 U
Net Weight	26.2 kg
Shipping Weight	30.16 kg
Shipping Height	250.0 mm
Shipping Width	590.0 mm
Shipping Depth	600.0 mm
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
Color	Black
Units per Pallet	16.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	42.000 dB
Online Thermal Dissipation	81.000 BTU/hr

Conformance

Approvals	C-tick , CE , EAC , GOST , GS Mark , IRAM , SABS , VDE
Standard warranty	2 years repair or replace

Equipment protection policy	Lifetime : \$150000
-----------------------------	---------------------

Sustainable Offer Status

RoHS	Compliant
------	-----------

REACH	REACH: Contains No SVHCs
-------	--------------------------

SMC2000I-2U_APC