



### Overview

|                      |   |
|----------------------|---|
| Model Name           | APC Smart-UPS 3000VA LCD 230V with SmartConnect |
| Includes             | CD with software                                |
| Standard Lead Time   | Usually in Stock                                |
| Product Distribution | Albania   |

### Output

|                                  |  |
|----------------------------------|--|
| Output Power Capacity            | 2700 Watts / 3000 VA                                     |
| Max Configurable Power (Watts)   | 2700 Watts / 3000 VA                                     |
| Nominal Output Voltage           | 230V   |
| Output Voltage Note              | Configurable for 220 : 230 or 240 nominal output voltage |
| Output Voltage Distortion        | Less than 5%   |
| Output Frequency (sync to mains) | 50/60Hz +/- 3 Hz   |
| Other Output Voltages            | 220, 240V  |
| Other Output Voltages            | Line Interactive   |
| Waveform Type                    | Sine wave  |
| Output Connections               | (1) IEC 320 C19 (Battery Backup)                         |

### Input

|  |                                  |
|--|----------------------------------|
| Nominal Input Voltage                              | 230V                             |
| Input Frequency                                    | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections                                  | British BS1363A                  |
| Input voltage range for main operations            | 160 - 286 V                      |
| Input voltage adjustable range for mains operation | 151 - 302V                       |
| Other Input Voltages                               | 220                              |

### Batteries & Runtime

|                       |  |
|-----------------------|--|
| Battery Type          | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Typical recharge time | 3 hour(s)  |
| Replacement Battery   | RBC55  |

|              |   |
|--------------|---|
| RBC Quantity | 1 |
|--------------|---|

## Communications & Management

|   |   |
|---|---|
| Interface Port(s)                       | SmartSlot   |
| Available SmartSlot™ Interface Quantity | 1   |
| Control panel                           | Multi-function LCD status and control console                               |
| Audible Alarm                           | Alarm when on battery : distinctive low battery alarm : configurable delays |
| Emergency Power Off (EPO)               | Yes   |

## Surge Protection and Filtering

|                     |  |
|---------------------|--|
| Surge energy rating | 365 Joules   |
| Filtering           | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |

## Physical

|                  |          |
|------------------|----------|
| Maximum Height   | 435.0 mm |
| Maximum Width    | 197.0 mm |
| Maximum Depth    | 544.0 mm |
| Net Weight       | 52.5 kg  |
| Shipping Weight  | 63.7 kg  |
| Shipping Height  | 699.0 mm |
| Shipping Width   | 381.0 mm |
| Shipping Depth   | 762.0 mm |
| Color            | Black    |
| Units per Pallet | 9.0      |

## Environmental

|   |                |
|---|----------------|
| Operating Environment                         | 0 - 40 °C      |
| Operating Relative Humidity                   | 0 - 95 %       |
| Operating Elevation                           | 0-3000 meters  |
| Storage Temperature                           | -15 - 45 °C    |
| Storage Relative Humidity                     | 0 - 95 %       |
| Storage Elevation                             | 0-15000 meters |
| Audible noise at 1 meter from surface of unit | 53.000 dB      |
| Online Thermal Dissipation                    | 375.000 BTU/hr |

## Conformance

|                   |  |
|-------------------|--|
| Approvals         | CE   |
| Standard warranty | 3 years repair or replace (excluding battery) and 2 year for battery |

## Sustainable Offer Status

|       |                          |
|-------|--------------------------|
| RoHS  | Compliant                |
| REACH | REACH: Contains No SVHCs |