

# Cisco Aironet 1540 Series Outdoor Access Points



# Contents

- Features and benefits 3
- Product specifications 4
- Ordering information 12
- Warranty information 12
- Cisco Wireless LAN Services 12
- Cisco Capital 13
- For more information 13



Cisco® Aironet® 1540 Series outdoor access points offer the latest 802.11ac Wave 2 functions in a rugged, ultra-low-profile housing that service providers and enterprises can deploy easily.

The Cisco Aironet 1540 Series is ideal for applications requiring rugged outdoor Wi-Fi coverage and supports the latest 802.11ac Wave 2 radio standard. Housed in a compact, aesthetically pleasing, easy-to-deploy package, the 1540 Series offers flexible deployment options for service providers and enterprise networks that need the fastest links possible for mobile outdoor clients (smartphones, tablets, and laptops) and wireless backhaul. The 1540 Series access points give network operators the flexibility to balance their desired wireless coverage with their need for easy deployment.

Whether deployed as a traditional access point or a wireless mesh access point, the 1540 Series provides the throughput capacity needed for today’s bandwidth-hungry devices.

## Features and benefits

By adhering to the 802.11ac Wave 2 standard, the 1540 Series provides a data rate of up to 867 Mbps on the 5-GHz radio. This exceeds the data rates offered by access points that support the 802.11n standard. It also enables a total aggregate dual-radio data rate of up to 1.1 Gbps. This provides the necessary foundation for enterprise and service provider networks to stay ahead of the performance expectations and needs of their wireless users.

In recent years corporate users have increasingly preferred wireless access as the form of network connectivity due to its convenience. With this shift, there is an expectation that wireless should not slow down users’ day-to-day work, but should enable a high-performance experience. The 1540 Series delivers this performance with highly secure and reliable wireless connections for mobile end users.

Table 1 lists the features and benefits of the 1540 Series.

**Table 1.** Features and benefits of Cisco Aironet 1540 Series

Feature	Benefit
<b>Compact size</b>	Enables deployment of the access point where it’s needed. The 1540 Series easily mounts to walls or light poles without disturbing the aesthetics of the area.
<b>802.11ac Wave 2 radio</b>	Provides up to 867-Mbps data rates with 2 x 2 Multiuser Multiple-Input, Multiple-Output (MU-MIMO) with up to two spatial streams.
<b>Multiuser MIMO (MU-MIMO)</b>	Allows transmission of data to multiple 802.11ac Wave 2-capable clients simultaneously to improve client experience. Prior to the 802.11ac Wave 2 standard, access points could transmit data to only one client at a time, typically referred to as single-user MIMO.

Feature	Benefit
<b>Flexible deployment modes</b>	Allows for deployment in a variety of ways, including as traditional access points and in mesh networks. The access points can also be deployed with the Cisco Mobility Express Solution. This deployment is ideal for small to medium-sized networks that require 50 or fewer access points without a physical controller. All deployment modes are easy to set up and configure.

The Cisco Aironet 1540 Series offers the following features:

- Compact, lightweight size: At just over 2.5 pounds (1 kg) and with a small footprint, the 1540 Series is one of the smallest outdoor access points with internal antennas.
- Low power consumption: Achieves full operation on standard 802.3af power (13.9W).
- Integrated antenna options: The 1540 Series offers two models with different antenna patterns to address a variety of use cases.

## Product specifications

Table 2 lists the specifications of the 1540 Series access points.

**Table 2.** Specifications

Item	Specifications
<b>802.11ac Wave 1 and 2 capabilities</b>	<ul style="list-style-type: none"> <li>• 1542I/D: 2 x 2 MIMO with two spatial streams</li> <li>• Multiuser and single-user MIMO</li> <li>• Maximal Ratio Combining (MRC)</li> <li>• 802.11ac beamforming (transmit beamforming)</li> <li>• 20-, 40-, and 80-MHz channels</li> <li>• PHY data rates up to 867 Mbps (80 MHz in 5 GHz)</li> <li>• Packet aggregation: A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx)</li> <li>• 802.11 Dynamic Frequency Selection (DFS)</li> <li>• Cyclic-Shift-Diversity (CSD) support</li> </ul>
<b>802.11n (and related) capabilities</b>	<ul style="list-style-type: none"> <li>• 1542I/D: 2 x 2 MIMO with two spatial streams</li> <li>• MRC</li> <li>• 20- and 40-MHz channels (40 MHz in 5 GHz)</li> <li>• PHY data rates up to 300 Mbps</li> <li>• Packet aggregation: A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx)</li> <li>• 802.11 DFS</li> <li>• CSD support</li> </ul>

Item	Specifications							
<b>Data rates supported</b>	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps							
	802.11b/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps							
	802.11n data rates on 2.4 and 5 GHz:							
	MCS Index	GI = 800 ns				GI = 400 ns		
		20-MHz Rates (Mbps)		40-MHz Rates (Mbps)		20-MHz Rates (Mbps)		40-MHz Rates (Mbps)
	0	6.5	13.5		7.2	15		
	1	13	27		14.4	30		
	2	19.5	40.5		21.7	45		
	3	26	54		28.9	60		
	4	39	81		43.3	90		
	5	52	108		57.8	120		
	6	58.5	121.5		65	135		
	7	65	135		72.2	150		
	8	13	27		14.4	30		
	9	26	54		28.9	60		
	10	39	81		43.3	90		
	11	58.5	108		57.8	120		
	12	78	162		86.7	180		
	13	104	216		115.6	240		
	14	117	243		130	270		
	15	130	270		144.4	300		
	802.11ac Data Rates (5 GHz)							
	Spatial Streams	MCS	GI = 800 ns			GI = 400 ns		
		20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz	
1	0	6.5	13.5	29.3	7.2	15	32.5	
1	1	13	27	58.5	14.4	30	65	
1	2	19.5	40.5	87.8	21.7	45	97.5	
1	3	26	54	117	28.9	60	130	
1	4	39	81	175.5	43.3	90	195	
1	5	52	108	234	57.8	120	260	
1	6	58.5	121.5	263.3	65	135	292.5	
1	7	65	135	292.5	72.2	150	325	
1	8	78	162	351	86.7	180	390	
1	9	-	180	390	-	200	433.3	

Item	Specifications							
	2	0	13	27	58.5	14.4	30	65
	2	1	26	54	117	28.9	60	130
	2	2	39	81	175.5	43.3	90	195
	2	3	52	108	234	57.8	120	260
	2	4	78	162	351	86.7	180	390
	2	5	104	216	468	115.6	240	520
	2	6	117	243	526.5	130	270	585
	2	7	130	270	585	144.4	300	650
	2	8	156	324	702	173.3	360	780
	2	9	-	360	780	-	400	866.7
<b>Frequency band and 20- MHz operating channels (regulatory domains)</b>	<p>A:  2.412 to 2.462 GHz, 11 channels  5.280 to 5.320 GHz, 3 channels  5.500 to 5.580 GHz, 5 channels  5.660 to 5.700 GHz, 3 channels  5.745 to 5.825 GHz, 5 channels</p> <p>B:  2.412 to 2.462 GHz, 11 channels  5.180 to 5.240 GHz, 4 channels  5.260 to 5.320 GHz, 4 channels  5.500 to 5.720 GHz, 12 channels  5.745 to 5.825 GHz, 5 channels</p> <p>C:  2.412 to 2.472 GHz, 13 channels  5.745 to 5.825 GHz, 5 channels</p> <p>D:  2.412 to 2.462 GHz, 11 channels  5.745 to 5.865 GHz, 7 channels</p> <p>E:  2.412 to 2.472 GHz, 13 channels  5.500 to 5.580 GHz, 5 channels  5.660 to 5.700 GHz, 3 channels</p> <p>F:  2.412 to 2.472 GHz, 13 channels  5.745 to 5.805 GHz, 4 channels</p> <p>G:  2.412 to 2.472 GHz, 13 channels  5.745 to 5.825 GHz, 5 channels</p> <p>H:  2.412 to 2.472 GHz, 13 channels</p>							

Item	Specifications
	<p>5.745 to 5.825 GHz, 5 channels</p> <p>I:</p> <p>2.412 to 2.472 GHz, 13 channels</p> <p>K:</p> <p>2.412 to 2.462 GHz, 11 channels</p> <p>5.280 to 5.320 GHz, 3 channels</p> <p>5.500 to 5.620 GHz, 7 channels</p> <p>5.745 to 5.805 GHz, 4 channels</p> <p><b>-I:</b></p> <p>2.412 to 2.472 GHz, 13 channels</p> <p>5.180 to 5.320 GHz, 8 channels</p> <p>L:</p> <p>2.412 to 2.472 GHz, 13 channels</p> <p>5.500 to 5.620 GHz, 7 channels</p> <p>5.745 to 5.865 GHz, 7 channels</p> <p>M:</p> <p>2.412 to 2.472 GHz, 13 channels</p> <p>5.500 to 5.580 GHz, 5 channels</p> <p>5.660 to 5.700 GHz, 3 channels</p> <p>5.745 to 5.805 GHz, 4 channels</p> <p><b>-N:</b></p> <p>2.412 to 2.462 GHz, 11 channels</p> <p>5.745 to 5.825 GHz, 5 channels</p> <p><b>-Q:</b></p> <p>2.412 to 2.472 GHz, 13 channels</p> <p>5.500 to 5.700 GHz, 11 channels</p> <p><b>-R:</b></p> <p>2.412 to 2.472 GHz, 13 channels</p> <p>5.260 to 5.320 GHz, 4 channels</p> <p>5.660 to 5.700 GHz, 3 channels</p> <p>5.745 to 5.825 GHz, 5 channels</p> <p><b>-S:</b></p> <p>2.412 to 2.472 GHz, 13 channels</p> <p>5.500 to 5.700 GHz, 11 channels</p> <p>5.745 to 5.825 GHz, 5 channels</p> <p><b>-T:</b></p> <p>2.412 to 2.462 GHz, 11 channels</p> <p>5.500 to 5.580 GHz, 5 channels</p> <p>5.660 to 5.700 GHz, 3 channels</p> <p>5.745 to 5.825 GHz, 5 channels</p> <p><b>-Z:</b></p> <p>2.412 to 2.462 GHz, 11 channels</p> <p>5.500 to 5.580 GHz, 5 channels</p>

Item	Specifications					
	5.660 to 5.700 GHz, 3 channels 5.745 to 5.825 GHz, 5 channels					
<b>Note:</b> Customers are responsible for verifying approval for use in their individual countries. To verify approval that corresponds to a particular country, please visit <a href="https://www.cisco.com/go/aironet/compliance">https://www.cisco.com/go/aironet/compliance</a> .						
<b>Maximum number of nonoverlapping channels</b>	<b>2.4 GHz</b>			<b>5 GHz</b>		
	<ul style="list-style-type: none"> <li>• 802.11b/g: <ul style="list-style-type: none"> <li>◦ 20 MHz: 3</li> </ul> </li> <li>• 802.11n: <ul style="list-style-type: none"> <li>◦ 20 MHz: 3</li> </ul> </li> </ul>			<ul style="list-style-type: none"> <li>• 802.11a: <ul style="list-style-type: none"> <li>◦ 20 MHz: 27</li> </ul> </li> <li>• 802.11n: <ul style="list-style-type: none"> <li>◦ 20 MHz: 27</li> <li>◦ 40 MHz: 13</li> </ul> </li> <li>• 802.11ac: <ul style="list-style-type: none"> <li>◦ 20 MHz: 27</li> <li>◦ 40 MHz: 13</li> <li>◦ 80 MHz: 6</li> </ul> </li> </ul>		
<b>Note:</b> This number varies by regulatory domain. Refer to the product documentation for specific details for each regulatory domain.						
<b>Clients Supported</b>	<b>200 per radio / 400 per access point</b>					
<b>Receive sensitivity</b>	Transmit Power and Receive Sensitivity (1542I and 1542D)					
			<b>2.4 GHz Radio</b>		<b>5 GHz Radio</b>	
		<b>Spatial Streams</b>	<b>Total TX Power (dBm)</b>	<b>RX Sensitivity (dBm)</b>	<b>Total TX Power (dBm)</b>	<b>RX Sensitivity (dBm)</b>
	<b>802.11/11b</b>					
	<b>1 Mbps</b>	1	27	-100	NA	NA
	<b>11 Mbps</b>	1	27	-92	NA	NA
	<b>802.11a/g</b>					
	<b>6 Mbps</b>	1	27	-95	25	-93
	<b>24 Mbps</b>	1	27	-89	25	-87
	<b>54 Mbps</b>	1	25	-79	24	-77
	<b>802.11n HT20</b>					
	<b>MCS0</b>	1	27	-95	25	-92
	<b>MCS4</b>	1	27	-84	25	-82
	<b>MCS7</b>	1	25	-76	23	-74
	<b>MCS8</b>	2	27	-94	25	-91
	<b>MCS12</b>	2	27	-82	25	-80
	<b>MCS15</b>	2	25	-74	23	-72
	<b>802.11n HT40</b>					
	<b>MCS0</b>	1			25	-90
	<b>MCS4</b>	1			25	-79



Item	Specifications				
MCS7	1			23	-72
MCS8	2			25	-89
MCS12	2			25	-77
MCS15	2			23	-70
<b>802.11ac VHT20</b>					
MCS0	1			25	-92
MCS4	1			24	-82
MCS7	1			21	-74
MCS8	1			20	-70
MCS0	2			25	-91
MCS4	2			24	-80
MCS7	2			21	-72
MCS8	2			20	-68
<b>802.11ac VHT40</b>					
MCS0	1			25	-90
MCS4	1			23	-79
MCS7	1			20	-72
MCS8	1			19	-68
MCS9	1			19	-66
MCS0	2			25	-89
MCS4	2			23	-77
MCS7	2			20	-70
MCS8	2			19	-66
MCS9	2			19	-64
<b>802.11ac VHT80</b>					
MCS0	1			25	-87
MCS4	1			23	-76
MCS7	1			21	-69
MCS8	1			19	-64
MCS9	1			19	-62
MCS0	2			25	-86
MCS4	2			23	-74
MCS7	2			21	-67
MCS8	2			19	-62
MCS9	2			19	-60

Item	Specifications		
<p><b>Note:</b> The maximum power setting will vary by channel and according to individual country regulations. Refer to the product documentation for specific details.</p>			
<b>Maximum conducted transmit power</b>	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%; vertical-align: top;"> <b>1542I</b> <ul style="list-style-type: none"> <li>• 2.4 GHz: 27 dBm with 2 antennas</li> <li>• 5 GHz: 25 dBm with 2 antennas</li> </ul> </td> <td style="width: 50%; vertical-align: top;"> <b>1542D</b> <ul style="list-style-type: none"> <li>• 2.4 GHz: 27 dBm with 2 antennas</li> <li>• 5 GHz: 25 dBm with 2 antennas</li> </ul> </td> </tr> </table>	<b>1542I</b> <ul style="list-style-type: none"> <li>• 2.4 GHz: 27 dBm with 2 antennas</li> <li>• 5 GHz: 25 dBm with 2 antennas</li> </ul>	<b>1542D</b> <ul style="list-style-type: none"> <li>• 2.4 GHz: 27 dBm with 2 antennas</li> <li>• 5 GHz: 25 dBm with 2 antennas</li> </ul>
<b>1542I</b> <ul style="list-style-type: none"> <li>• 2.4 GHz: 27 dBm with 2 antennas</li> <li>• 5 GHz: 25 dBm with 2 antennas</li> </ul>	<b>1542D</b> <ul style="list-style-type: none"> <li>• 2.4 GHz: 27 dBm with 2 antennas</li> <li>• 5 GHz: 25 dBm with 2 antennas</li> </ul>		
<p><b>Note:</b> The maximum power setting will vary by channel and according to individual country regulations. Refer to the product documentation for specific details.</p>			
<b>Interfaces</b>	<ul style="list-style-type: none"> <li>• WAN port 10/100/1000BASE-T Ethernet, autosensing (RJ-45), PoE in</li> <li>• Management console port (RJ-45)</li> <li>• Multicolor LED/Reset button</li> </ul>		
<b>Uplink options</b>	Ethernet and wireless mesh		
<b>Dimensions (L x W x H)</b>	1542I/D: 7.9 x 5.9 x 2.4 in.(20 x 15 x 6.1 cm)		
<b>Weight</b>	1542I/D: 2.75 lb (1.25 kg)		
<b>Environmental</b>	<p>Operating temperature:</p> <ul style="list-style-type: none"> <li>• -40° to 65° C (-40° to 149° F) ambient air with no solar loading</li> <li>• -40° to 55° C (-40° to 131° F) ambient air with solar loading</li> <li>• Storage temperature: -40° to 85° C (-40° to 185° F)</li> </ul> <p>Humidity:</p> <ul style="list-style-type: none"> <li>• 5 - 95% non-condensing</li> </ul> <p>Wind resistance:</p> <ul style="list-style-type: none"> <li>• Up to 100-mph sustained winds</li> <li>• Up to 165-mph wind gusts</li> </ul>		
<b>Environmental ratings</b>	<ul style="list-style-type: none"> <li>• IEC 60529 IP67</li> <li>• Icing protection            NEMA 250-2008</li> <li>• Corrosion                    NEMA 250-2008 (600 hours)</li> <li>• Solar radiation            EN 60068-2-5 (1200 W/m2)</li> <li>• Vibration                    MIL-STD-810</li> </ul>		
<b>Antennas</b>	<ul style="list-style-type: none"> <li>• 1542I: Integrated dual-band, vertical polarization, omnidirectional antenna radome, 5 dBi (2.4 Ghz) and 5dBi (5.8 GHz)**</li> <li>• 1542D: Integrated dual-band, dual polarization, directional antenna radome, vertically polarized 8 dBi (2.4 GHz), 9 dBi (5 GHz)</li> </ul> <p>** This model can be mounted horizontally on a wall or pole, to provide omni-directional coverage; or can be mounted vertically to provide semi-omni coverage.</p>		
<b>Powering options</b>	<ul style="list-style-type: none"> <li>• 802.3af, 802.3at</li> <li>• Cisco power injectors: <ul style="list-style-type: none"> <li>◦ AIR-PWRINJ-60RGD1= (outdoor rated, 60W, with NEMA 5-15 AC plug)</li> <li>◦ AIR-PWRINJ-60RGD2= (outdoor rated, 60W, unterminated AC cable)</li> <li>◦ AIR-PWRINJ5= (indoor, 802.3af)</li> <li>◦ AIR-PWRINJ6= (indoor, 802.3at)</li> </ul> </li> </ul>		
<b>Power consumption</b>	Max power draw is 13.9W with 100 meters Category 5 cable		

Item	Specifications
<b>Compliance</b>	<p><b>Safety</b></p> <ul style="list-style-type: none"> <li>• UL60950, 2<sup>nd</sup> Edition</li> <li>• CAN/CSA-C22.2 No. 60950, 2<sup>nd</sup> Edition</li> <li>• IEC 60950, 2<sup>nd</sup> Edition</li> <li>• EN 60950, 2<sup>nd</sup> Edition</li> </ul> <p><b>Immunity</b></p> <ul style="list-style-type: none"> <li>• &lt;= 5 mJ f or 6kV/3kA @ 8/20 ms waveform</li> <li>• ANSI/IEEE C62.41</li> <li>• EN61000-4-5 Lev el 4 AC Surge Immunity</li> <li>• EN61000-4-4 Lev el 4 Electrical Fast Transient Burst Immunity</li> <li>• EN61000-4-3 Lev el 4 EMC Field Immunity</li> <li>• EN61000-4-2 Lev el 2 ESD Immunity</li> <li>• EN60950 Overvoltage Category IV</li> </ul> <p><b>Radio Approvals</b></p> <ul style="list-style-type: none"> <li>• FCC Part 15.247, 15.407</li> <li>• FCC Bulletin OET-65C</li> <li>• RSS-210</li> <li>• RSS-102</li> <li>• AS/NZS 4268.2003</li> <li>• ARIB-STD 66 (Japan)</li> <li>• ARIB-STD T71 (Japan)</li> <li>• EN 300 328</li> <li>• EN 301 893</li> </ul> <p><b>EMI and Susceptibility</b></p> <ul style="list-style-type: none"> <li>• FCC part 15.107, 15.109</li> <li>• ICES-003</li> <li>• EN 301 489-1, -17</li> </ul> <p><b>Security</b></p> <ul style="list-style-type: none"> <li>• Wireless bridging/mesh</li> <li>• X.509 digital certificates</li> <li>• MAC address authentication</li> <li>• Advanced Encryption Standard (AES)</li> </ul> <p><b>Wireless Access</b></p> <ul style="list-style-type: none"> <li>• 802.11i, Wi-Fi Protected Access 2 (WPA2), and WPA</li> <li>• 802.1X authentication, including Extensible Authentication Protocol (EAP) and Protected EAP (EAP -PEAP), EAP Transport Layer Security (EAP-TLS), EAP-Tunneled TLS (EAP-TTLS), EAP-Subscriber Identity Module (EAP-SIM), and Cisco LEAP</li> <li>• VPN pass-through</li> <li>• IP Security (IPsec)</li> <li>• Layer 2 Tunneling Protocol (L2TP)</li> <li>• MAC address filtering</li> </ul>
<b>Warranty</b>	1-year limited hardware warranty

## Ordering information

Table 3 gives ordering information for the Cisco Aironet 1540 Series.

**Table 3.** Ordering information

Part Number	Product Description
<b>Aironet 1540 Series</b>	<ul style="list-style-type: none"><li>• AIR-AP1542I-x-K9: Dual-band 802.11a/g/n/ac, Wave 2, internal omni antennas</li><li>• AIR-AP1542D-x-K9: Dual-band 802.11a/g/n/ac, Wave 2, internal directional antennas</li></ul> <p>Regulatory domains: (x = regulatory domain).</p> <p>Customers are responsible for verifying approval for use in their individual countries. To verify approval that corresponds to a particular country or the regulatory domain used in a specific country, visit <a href="https://www.cisco.com/go/aironet/compliance">https://www.cisco.com/go/aironet/compliance</a>.</p> <p>Not all regulatory domains have been approved. As they are approved, the part numbers will be available on the Global Price List.</p> <p><b>Cisco Smart Net Total Care™ Service for the Cisco Aironet 1540 Series Access Points</b></p> <p>Refer to the service part numbers on Cisco Commerce Workspace for available service offerings.</p>

## Warranty information

The Cisco Aironet 1540 Series access points come with a 1 -year limited warranty that provides full warranty coverage of the hardware. The warranty includes 10 -day advance hardware replacement and helps ensure that software media are defect-free for 90 days. For more details, visit <https://www.cisco.com/go/warranty>.

## Cisco Wireless LAN Services

Realize the full business value of your technology investments faster with intelligent, customized services from Cisco. Backed by deep networking expertise, Cisco Wireless LAN Services enable you to deploy a sound, scalable mobility network that enables rich media collaboration while improving the operational efficiency gained from a converged wired and wireless network infrastructure based on the Cisco Unified Wireless Network. We offer expert advisory, implementation and optimization services to accelerate your transition to advanced mobility services while continuously optimizing the performance, reliability, and security of that architecture after it is deployed. In addition, Smart Net Total Care service helps you protect your investment and derive maximum value from your Cisco products. Delivered by Cisco and backed by your trusted partner, this comprehensive service includes access to the Cisco Technical Assistance Center 24 hours a day, 365 days a year, IOS software updates, online resources, and expedited hardware replacement when needed. The Smart Net Total Care service helps you solve problems faster, improve operational efficiency, and reduce the risk of downtime. For more details, visit: <https://www.cisco.com/c/en/us/products/wireless/service-listing.html>.

---

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)

### For more information

For more information about the Cisco Aironet 1540 Series, visit <https://www.cisco.com/go/wireless> or contact your local Cisco account representative.

#### Americas Headquarters

Cisco Systems, Inc.  
San Jose, CA

#### Asia Pacific Headquarters

Cisco Systems (USA) Pte. Ltd.  
Singapore

#### Europe Headquarters

Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)